

Technical Data Sheet  
Electric Motor Three phase in Cast Iron IE1



L (standard motor)

355

L (motor w/brake)

465

L (motor w/forced ventilation)

460

L (motor without ventilation)

345

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
90	140	100	56	10	24j6	50	8	20	27	M8x19	180	140	177	250	-	-	-	-	-

### Electrical Data

Type	EM30 90S-8	
Poles	8/750	Poles
Power	0.37	Kw
Voltage	400	V
Frequency	50	Hz
Speed	675	rpm
Nominal current	1.41	A
Power factor	0.61	
Efficiency 100%	62.0	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	5.23	N.m
Ta/Tn	1.8	
Ia/In	4.0	
Tm/Tn	1.9	

### Mechanical Data

Shaft height	90
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	56 dB(A)
Weight	20 kg
Bearing DE	6205 2Z C3
Bearing NDE	6205 2Z C3

### Extra Data

#### Applicable brakes

DC brake	REB-05-10	Brake torque	16	N.m
AC brake	AC4	Brake torque	20	N.m

#### Applicable forced ventilations

Single-phase forced ventilation	Power	45	W
Three-phase forced ventilation	Power	45	W

Universal Motors S.A.  
Rua Comendador Brandão, 484  
4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
TEL.: 252 299 080

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Road  
West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
TEL.: +44(0) 1484660222

Universal Motors SL  
C/La Habana n.6 nave 4 PI Camporoso  
28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
TEL.: 918 864 213