



L (standard motor)
410
 L (motor w/brake)
525
 L (motor w/forced ventilation)
510
 L (motor without ventilation)
390

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
100	160	140	63	12	28j6	60	8	24	31	M10x22	205	175	198	270	-	-	-	-	-

Electrical Data

Type	HE30 100L-2	
Poles	2/3000	Poles
Power	3.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2880	rpm
Nominal current	5.90	A
Power factor	0.87	
Efficiency 100%	84.6	%
Efficiency 75%	85.8	%
Efficiency 50%	84.1	%
Torque	9.949999999999999N.m	
Ta/Tn	2.2	
Ia/In	7.8	
Tm/Tn	2.3	

Mechanical Data

Shaft height	100	
Construction form	B3	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S3-70%	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	74	dB(A)
Weight	38	kg
Bearing DE	6206 2Z C3	
Bearing NDE	6206 2Z C3	

Extra Data

Applicable brakes

DC brake	REB-05-12	Brake torque	32	N.m
AC brake	AC5	Brake torque	40	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	65	W
Three-phase forced ventilation	Power	65	W