


Technical Data Sheet  
Electric Motor Three phase in Cast Iron IE1



L (standard motor)

475

L (motor w/brake)

590

L (motor w/forced ventilation)

550

L (motor without ventilation)

420

| Feet |     |     |    |    | Shaft |    |    |    |    |        | Carcass |     |     |     | Flange |   |   |   |   |
|------|-----|-----|----|----|-------|----|----|----|----|--------|---------|-----|-----|-----|--------|---|---|---|---|
| H    | A   | B   | C  | K  | D     | E  | F  | G  | GA | X      | AB      | BB  | AC  | HD  | M      | N | P | S | T |
| 132  | 216 | 140 | 89 | 12 | 38k6  | 80 | 10 | 33 | 41 | M12x28 | 270     | 185 | 259 | 349 | -      | - | - | - | - |

### Electrical Data

|                 |             |       |
|-----------------|-------------|-------|
| Type            | EM30 132S-6 |       |
| Poles           | 6/1000      | Poles |
| Power           | 3.00        | Kw    |
| Voltage         | 400         | V     |
| Frequency       | 50          | Hz    |
| Speed           | 960         | rpm   |
| Nominal current | 7.03        | A     |
| Power factor    | 0.76        |       |
| Efficiency 100% | 81.0        | %     |
| Efficiency 75%  | -           | %     |
| Efficiency 50%  | -           | %     |
| Torque          | 29.84       | N.m   |
| Ta/Tn           | 2.1         |       |
| Ia/In           | 6.5         |       |
| Tm/Tn           | 2.1         |       |

### Mechanical Data

|                       |            |       |
|-----------------------|------------|-------|
| Shaft height          | 132        |       |
| Construction form     | B3         |       |
| Mechanical protection | 55         |       |
| Heating class         | B          |       |
| Insulation class      | F          |       |
| Service               | S3-70%     |       |
| Ambient temp.         | -10°C-40°C |       |
| Altitude              | 1000       |       |
| Noise                 | 69         | dB(A) |
| Weight                | 59         | kg    |
| Bearing DE            | 6308 2Z C3 |       |
| Bearing NDE           | 6308 2Z C3 |       |

### Extra Data

#### Applicable brakes

|          |           |              |    |     |
|----------|-----------|--------------|----|-----|
| DC brake | REB-05-16 | Brake torque | 80 | N.m |
| AC brake | AC7       | Brake torque | 90 | N.m |

#### Applicable forced ventilations

|                                 |       |    |   |
|---------------------------------|-------|----|---|
| Single-phase forced ventilation | Power | 55 | W |
| Three-phase forced ventilation  | Power | 55 | W |

Universal Motors S.A.  
Rua Comendador Brandão, 484  
4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
TEL.: 252 299 080

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Road  
West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
TEL.: +44(0) 1484660222

Universal Motors SL  
C/La Habana n.6 nave 4 PI Camporoso  
28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
TEL.: 918 864 213