

Technical Data Sheet  
 Electric Motor Three phase in Cast Iron IE1



L (standard motor)

515

L (motor w/brake)

660

L (motor w/forced ventilation)

620

L (motor without ventilation)

488

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
132	216	178	89	12	38k6	80	10	33	41	M12x28	270	225	259	349	-	-	-	-	-

**Electrical Data**

Type	EM30 132M1-6
Poles	6/1000 Poles
Power	4.00 Kw
Voltage	400 V
Frequency	50 Hz
Speed	960 rpm
Nominal current	9.26 A
Power factor	0.76
Efficiency 100%	82.0 %
Efficiency 75%	- %
Efficiency 50%	- %
Torque	39.79 N.m
Ta/Tn	2.1
Ia/In	6.5
Tm/Tn	2.1

**Mechanical Data**

Shaft height	132
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	69 dB(A)
Weight	66 kg
Bearing DE	6308 2Z C3
Bearing NDE	6308 2Z C3

**Extra Data**

**Applicable brakes**

DC brake	REB-05-16	Brake torque	80	N.m
AC brake	AC7	Brake torque	90	N.m

**Applicable forced ventilations**

Single-phase forced ventilation	Power	55	W
Three-phase forced ventilation	Power	55	W

Universal Motors S.A.  
 Rua Comendador Brandão, 484  
 4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
 TEL.: 252 299 080

Universal Motors UK, Ltd  
 Unit E2, Meltham Mills Road  
 West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
 TEL.: +44(0) 1484660222

Universal Motors SL  
 C/La Habana n.6 nave 4 PI Camporoso  
 28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
 TEL.: 918 864 213