


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE1



L (standard motor)

930

L (motor w/brake)

1130

L (motor w/forced ventilation)

1050

L (motor without ventilation)

830

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
250	406	349	168	24	65m6	140	18	58	69	M20x42	490	485	485	615	-	-	-	-	-

Electrical Data

Type	EM30 250M-6	
Poles	6/1000	Poles
Power	37.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	980	rpm
Nominal current	67.50	A
Power factor	0.86	
Efficiency 100%	92.0	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	360.53	N.m
Ta/Tn	2.1	
Ia/In	7.0	
Tm/Tn	2.1	

Mechanical Data

Shaft height	250
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	78 dB(A)
Weight	355 kg
Bearing DE	6314 C3
Bearing NDE	6314 C3

Extra Data

Applicable brakes

DC brake	K10	Brake torque	500-800	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	200	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213