

Technical Data Sheet  
 Electric Motor Three phase in Cast Iron IE2



L (standard motor)

1030

L (motor w/brake)

1240

L (motor w/forced ventilation)

1185

L (motor without ventilation)

910

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
280	457	368	190	14	75m6	140	20	67.5	79.5	M20x42	550	485	547	680	-	-	-	-	-

**Electrical Data**

Type	HE30 280S-8	
Poles	8/750	Poles
Power	37.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	740	rpm
Nominal current	74.90	A
Power factor	0.79	
Efficiency 100%	90.3	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	477.46	N.m
Ta/Tn	1.9	
Ia/In	6.6	
Tm/Tn	2	

**Mechanical Data**

Shaft height	280
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	76 dB(A)
Weight	537 kg
Bearing DE	6317 C3
Bearing NDE	6317 C3

**Extra Data**

**Applicable brakes**

DC brake	K10D	Brake torque	1000/1500 N.m
AC brake	NA	Brake torque	NA N.m

**Applicable forced ventilations**

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	270	W

Universal Motors S.A.  
 Rua Comendador Brandão, 484  
 4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
 TEL.: 252 299 080

Universal Motors UK, Ltd  
 Unit E2, Meltham Mills Road  
 West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
 TEL.: +44(0) 1484660222

Universal Motors SL  
 C/La Habana n.6 nave 4 PI Camporoso  
 28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
 TEL.: 918 864 213