



L (standard motor)
 1235
 L (motor w/brake)
 1445
 L (motor w/forced ventilation)
 1415
 L (motor without ventilation)
 1060

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
315	508	406	216	28	80m6	170	22	71	85	M20x42	635	565	620	845	-	-	-	-	-

Electrical Data

Type	HE30 315S-8	
Poles	8/750	Poles
Power	55.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	735	rpm
Nominal current	107.70	A
Power factor	0.81	
Efficiency 100%	91.0	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	714.5700000000001N.m	
Ta/Tn	1.8	
Ia/In	6.6	
Tm/Tn	2	

Mechanical Data

Shaft height	315
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	82 dB(A)
Weight	937 kg
Bearing DE	NU 319
Bearing NDE	6319 C3

Extra Data

Applicable brakes

DC brake	K10D	Brake torque	1000/1500 N.m
AC brake	NA	Brake torque	NA N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	450	W