

Technical Data Sheet
 Electric Motor Three phase in Cast Iron IE1



L (standard motor)
1235

L (motor w/brake)
1445

L (motor w/forced ventilation)
1415

L (motor without ventilation)
1060

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
315	508	406	216	28	80m6	170	22	71	85	M20x42	635	565	620	845	-	-	-	-	-

Electrical Data

Type	EM30 315S-6
Poles	6/1000 Poles
Power	75.00 Kw
Voltage	400 V
Frequency	50 Hz
Speed	985 rpm
Nominal current	135.00 A
Power factor	0.86
Efficiency 100%	93.5 %
Efficiency 75%	- %
Efficiency 50%	- %
Torque	727.1 N.m
Ta/Tn	2
Ia/In	6.7
Tm/Tn	2

Mechanical Data

Shaft height	315
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	85 dB(A)
Weight	859 kg
Bearing DE	NU 319
Bearing NDE	6319 C3

Extra Data

Applicable brakes

DC brake	K11D	Brake torque	2000/2800 N.m
AC brake	NA	Brake torque	NA N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA W
Three-phase forced ventilation	Power	450 W

Universal Motors S.A.
 Rua Comendador Brandão, 484
 4495-375 Póvoa de Varzim
geral@universalmotors.pt
 TEL.: 252 299 080

Universal Motors UK, Ltd
 Unit E2, Meltham Mills Road
 West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
 TEL.: +44(0) 1484660222

Universal Motors SL
 C/La Habana n.6 nave 4 PI Camporoso
 28806 Alcala de Henares
info@universalmotors-group.es
 TEL.: 918 864 213