

Technical Data Sheet  
 Electric Motor Three phase in Cast Iron IE1



L (standard motor)

1535

L (motor w/brake)

1775

L (motor w/forced ventilation)

1770

L (motor without ventilation)

1400

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
355	610	560	254	28	95m6	170	25	86	101	M20x42	730	755	698	1010	-	-	-	-	-

**Electrical Data**

Type	EM30 355M2-8	
Poles	8/750	Poles
Power	160.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	740	rpm
Nominal current	299.00	A
Power factor	0.82	
Efficiency 100%	94.2	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	2064.71	N.m
Ta/Tn	1.8	
Ia/In	6.4	
Tm/Tn	2	

**Mechanical Data**

Shaft height	355
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	90 dB(A)
Weight	1658 kg
Bearing DE	NU 322
Bearing NDE	6322 C3

**Extra Data**

**Applicable brakes**

DC brake	K12D	Brake torque	4500	N.m
AC brake	NA	Brake torque	NA	N.m

**Applicable forced ventilations**

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	700	W

Universal Motors S.A.  
 Rua Comendador Brandão, 484  
 4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
 TEL.: 252 299 080

Universal Motors UK, Ltd  
 Unit E2, Meltham Mills Road  
 West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
 TEL.: +44(0) 1484660222

Universal Motors SL  
 C/La Habana n.6 nave 4 PI Camporoso  
 28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
 TEL.: 918 864 213