

Technical Data Sheet
 Electric Motor Three phase in Cast Iron IE4



L (standard motor)

1505

L (motor w/brake)

NA

L (motor w/forced ventilation)

1740

L (motor without ventilation)

1370

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
355	610	630	254	28	75m6	140	20	67.5	79.5	M20x42	730	755	698	1010	-	-	-	-	-

Electrical Data

Type	UM4C 355L-2	
Poles	2/3000	Poles
Power	315.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2980	rpm
Nominal current	517.77	A
Power factor	0.91	
Efficiency 100%	96.5	%
Efficiency 75%	96.4	%
Efficiency 50%	95.5	%
Torque	1009.4	N.m
Ta/Tn	1.6	
Ia/In	8.5	
Tm/Tn	2.2	

Mechanical Data

Shaft height	355
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	97 dB(A)
Weight	1880 kg
Bearing DE	6319 C3
Bearing NDE	6319 C3

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	700	W

Universal Motors S.A.
 Rua Comendador Brandão, 484
 4495-375 Póvoa de Varzim
geral@universalmotors.pt
 TEL.: 252 299 080

Universal Motors UK, Ltd
 Unit E2, Meltham Mills Road
 West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
 TEL.: +44(0) 1484660222

Universal Motors SL
 C/La Habana n.6 nave 4 PI Camporoso
 28806 Alcala de Henares
info@universalmotors-group.es
 TEL.: 918 864 213