


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE4



- L (standard motor)
685
- L (motor w/brake)
795
- L (motor w/forced ventilation)
805
- L (motor without ventilation)
595

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
160	254	210	108	15	42k6	110	12	37	45	M16x36	320	258	315	420	-	-	-	-	-

Electrical Data			Mechanical Data		
Type	UM4C 160M-6		Shaft height	160	
Poles	6/1000	Poles	Construction form	B3	
Power	7.50	Kw	Mechanical protection	55	
Voltage	400	V	Heating class	B	
Frequency	50	Hz	Insulation class	F	
Speed	980	rpm	Service	S1	
Nominal current	15.60	A	Ambient temp.	-10°C-40°C	
Power factor	0.76		Altitude	1000	
Efficiency 100%	91.3	%	Noise	73	dB(A)
Efficiency 75%	89.6	%	Weight	126	kg
Efficiency 50%	88.4	%	Bearing DE	6309 C3	
Torque	73.09999999999999N.m		Bearing NDE	6309 C3	
Ta/Tn	2				
Ia/In	8.0				
Tm/Tn	2.1				

Extra Data

Applicable brakes

DC brake	K8	Brake torque	200	N.m
AC brake	AC8	Brake torque	200	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	60	W