


Technical Data Sheet  
Electric Motor Three phase in Cast Iron IE4



L (standard motor)

795

L (motor w/brake)

990

L (motor w/forced ventilation)

950

L (motor without ventilation)

700

| Feet |     |     |     |    | Shaft |     |    |    |    |        | Carcass |     |     |     | Flange |   |   |   |   |
|------|-----|-----|-----|----|-------|-----|----|----|----|--------|---------|-----|-----|-----|--------|---|---|---|---|
| H    | A   | B   | C   | K  | D     | E   | F  | G  | GA | X      | AB      | BB  | AC  | HD  | M      | N | P | S | T |
| 200  | 318 | 305 | 133 | 19 | 55m6  | 110 | 16 | 49 | 59 | M20x42 | 385     | 370 | 397 | 505 | -      | - | - | - | - |

### Electrical Data

|                 |                      |       |
|-----------------|----------------------|-------|
| Type            | UM4C 200L-8          |       |
| Poles           | 8/750                | Poles |
| Power           | 15.00                | Kw    |
| Voltage         | 400                  | V     |
| Frequency       | 50                   | Hz    |
| Speed           | 735                  | rpm   |
| Nominal current | 31.60                | A     |
| Power factor    | 0.75                 |       |
| Efficiency 100% | 91.2                 | %     |
| Efficiency 75%  | 89.4                 | %     |
| Efficiency 50%  | 88.5                 | %     |
| Torque          | 194.897959183673 N.m |       |
| Ta/Tn           | 1.8                  |       |
| Ia/In           | 8.0                  |       |
| Tm/Tn           | 2                    |       |

### Mechanical Data

|                       |            |       |
|-----------------------|------------|-------|
| Shaft height          | 200        |       |
| Construction form     | B3         |       |
| Mechanical protection | 55         |       |
| Heating class         | B          |       |
| Insulation class      | F          |       |
| Service               | S1         |       |
| Ambient temp.         | -10°C-40°C |       |
| Altitude              | 1000       |       |
| Noise                 | 73         | dB(A) |
| Weight                | 277        | kg    |
| Bearing DE            | 6312 C3    |       |
| Bearing NDE           | 6312 C3    |       |

### Extra Data

#### Applicable brakes

|          |      |              |     |     |
|----------|------|--------------|-----|-----|
| DC brake | K8D  | Brake torque | 400 | N.m |
| AC brake | AC8D | Brake torque | 400 | N.m |

#### Applicable forced ventilations

|                                 |       |     |   |
|---------------------------------|-------|-----|---|
| Single-phase forced ventilation | Power | NA  | W |
| Three-phase forced ventilation  | Power | 110 | W |

Universal Motors S.A.  
Rua Comendador Brandão, 484  
4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
TEL.: 252 299 080

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Road  
West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
TEL.: +44(0) 1484660222

Universal Motors SL  
C/La Habana n.6 nave 4 PI Camporoso  
28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
TEL.: 918 864 213