


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

930

L (motor w/brake)

1095

L (motor w/forced ventilation)

1060

L (motor without ventilation)

810

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
225	356	311	149	19	60m6	140	18	53	64	M20x42	435	445	445	560	-	-	-	-	-

Electrical Data

Type	PE30/UM3C*
	225M-4
Poles	4/1500
Power	45.00
Voltage	400
Frequency	50
Speed	1485
Nominal current	80.20
Power factor	0.86
Efficiency 100%	94.2
Efficiency 75%	94.6
Efficiency 50%	93.4
Torque	289.4
Ta/Tn	2
Ia/In	7.4
Tm/Tn	2.3

Mechanical Data

Shaft height	225
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	78
Weight	373
Bearing DE	6313 C3
Bearing NDE	6313 C3

Extra Data

Applicable brakes

DC brake	K9D	Brake torque	600	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	170	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 Pl Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213