

Technical Data Sheet  
Electric Motor Three phase in Cast Iron IE4



L (standard motor)

1040

L (motor w/brake)

1250

L (motor w/forced ventilation)

1195

L (motor without ventilation)

920

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
280	457	368	190	14	75m6	140	20	67.5	79.5	M20x42	550	485	547	680	-	-	-	-	-

### Electrical Data

Type	UM4C 280S-8	
Poles	8/750	Poles
Power	37.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	740	rpm
Nominal current	73.50	A
Power factor	0.78	
Efficiency 100%	93.1	%
Efficiency 75%	93.2	%
Efficiency 50%	92.2	%
Torque	477.5	N.m
Ta/Tn	1.8	
Ia/In	7.9	
Tm/Tn	2	

### Mechanical Data

Shaft height	280
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	76 dB(A)
Weight	572 kg
Bearing DE	6317 C3
Bearing NDE	6317 C3

### Extra Data

#### Applicable brakes

DC brake	K10D	Brake torque	1000/1500 N.m
AC brake	NA	Brake torque	NA N.m

#### Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	270	W

Universal Motors S.A.  
Rua Comendador Brandão, 484  
4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
TEL.: 252 299 080

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Road  
West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
TEL.: +44(0) 1484660222

Universal Motors SL  
C/La Habana n.6 nave 4 PI Camporoso  
28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
TEL.: 918 864 213