


Technical Data Sheet
Electric Motor Three phase in Cast Iron IE3



L (standard motor)

1235

L (motor w/brake)

1445

L (motor w/forced ventilation)

1415

L (motor without ventilation)

1060

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
315	508	406	216	28	80m6	170	22	71	85	M20x42	635	565	620	845	-	-	-	-	-

Electrical Data

Type	PE30/UM3C* 315S-6	
Poles	6/1000	Poles
Power	75.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	985	rpm
Nominal current	136.30	A
Power factor	0.84	
Efficiency 100%	94.6	%
Efficiency 75%	94.7	%
Efficiency 50%	93.4	%
Torque	727.1	N.m
Ta/Tn	2	
Ia/In	6.6	
Tm/Tn	2	

Mechanical Data

Shaft height	315
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	83 dB(A)
Weight	791 kg
Bearing DE	NU 319
Bearing NDE	6319 C3

Extra Data

Applicable brakes

DC brake	K11D	Brake torque	2000/2800 N.m
AC brake	NA	Brake torque	NA N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	450	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213