

Technical Data Sheet
 Electric Motor Three phase in Aluminum IE3



L (standard motor)

384

L (motor w/brake)

460

L (motor w/forced ventilation)

495

L (motor without ventilation)

339

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
100	160	140	63	12	28j6	60	8	24	31	M10x22	198	176	205	252	-	-	-	-	-

Electrical Data

Type	PE31/UM3A* 100L-2	
Poles	2/3000	Poles
Power	3.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2915	rpm
Nominal current	5.71	A
Power factor	0.87	
Efficiency 100%	87.1	%
Efficiency 75%	87.3	%
Efficiency 50%	86.4	%
Torque	9.83	N.m
Ta/Tn	2.3	
Ia/In	8.1	
Tm/Tn	2.3	

Mechanical Data

Shaft height	100
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	82 dB(A)
Weight	26 kg
Bearing DE	6206 2Z C3
Bearing NDE	6206 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-12	Brake torque	32	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	65	W
Three-phase forced ventilation	Power	65	W

Universal Motors S.A.
 Rua Comendador Brandão, 484
 4495-375 Póvoa de Varzim
geral@universalmotors.pt
 TEL.: 252 299 080

Universal Motors UK, Ltd
 Unit E2, Meltham Mills Road
 West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
 TEL.: +44(0) 1484660222

Universal Motors SL
 C/La Habana n.6 nave 4 PI Camporoso
 28806 Alcala de Henares
info@universalmotors-group.es
 TEL.: 918 864 213