



L (standard motor)

400

L (motor w/brake)

470

L (motor w/forced ventilation)

510

L (motor without ventilation)

342

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
112	190	140	70	12	28j6	60	8	24	31	M10x22	227	183	220	279	-	-	-	-	-

Electrical Data

Type	UM4A 112M-6	
Poles	6/1000	Poles
Power	2.20	Kw
Voltage	400	V
Frequency	50	Hz
Speed	970	rpm
Nominal current	5.27	A
Power factor	0.69	
Efficiency 100%	87.4	%
Efficiency 75%	87.2	%
Efficiency 50%	85.4	%
Torque	21.66	N.m
Ta/Tn	3.1	
Ia/In	7.4	
Tm/Tn	3.9	

Mechanical Data

Shaft height	112
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	64 dB(A)
Weight	35 kg
Bearing DE	6306 ZZ C3
Bearing NDE	6206 ZZ C3

Extra Data

Applicable brakes

DC brake	REB-05-14	Brake torque	60	N.m
AC brake	AC6	Brake torque	60	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	80	W
Three-phase forced ventilation	Power	80	W