



L (standard motor)

500

L (motor w/brake)

590

L (motor w/forced ventilation)

620

L (motor without ventilation)

438

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
132	216	178	89	12	38k6	80	10	33	41	M12x18	265	230	259	318	-	-	-	-	-

### Electrical Data

Type	UM3A 132M2-6	
Poles	6/1000	Poles
Power	5.50	Kw
Voltage	400	V
Frequency	50	Hz
Speed	975	rpm
Nominal current	12.70	A
Power factor	0.71	
Efficiency 100%	88.0	%
Efficiency 75%	88.3	%
Efficiency 50%	87.1	%
Torque	53.9	N.m
Ta/Tn	2.9	
Ia/In	7.4	
Tm/Tn	3.5	

### Mechanical Data

Shaft height	132
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	68 dB(A)
Weight	55.7 kg
Bearing DE	6308 ZZ C3
Bearing NDE	6208 ZZ C3

### Extra Data

#### Applicable brakes

DC brake	REB-05-16	Brake torque	80	N.m
AC brake	AC7	Brake torque	90	N.m

#### Applicable forced ventilations

Single-phase forced ventilation	Power	55	W
Three-phase forced ventilation	Power	55	W