

Technical Data Sheet
 Electric Motor Three phase in Aluminum -



L (standard motor)

500

L (motor w/brake)

590

L (motor w/forced ventilation)

620

L (motor without ventilation)

438

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
132	216	178	89	12	38k6	80	10	33	41	M12x18	265	230	259	318	-	-	-	-	-

Electrical Data

Type	UMDA 132M-4/8	
Poles	4/8	Poles
Power	7,5 / 1,5	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1450 / 720	rpm
Nominal current	14,47 / 5,11	A
Power factor	0,86 / 0,55	
Efficiency 100%	87 / 77	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	49,4 / 19,9	N.m
Ta/Tn	2,0 / 1,7	
Ia/In	6,8 / 3,0	
Tm/Tn	2,7 / 2,2	

Mechanical Data

Shaft height	132
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	- dB(A)
Weight	49.6 kg
Bearing DE	6308 ZZ C3
Bearing NDE	6208 ZZ C3

Extra Data

Applicable brakes

DC brake	REB-05-16	Brake torque	80	N.m
AC brake	AC7	Brake torque	90	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	55	W
Three-phase forced ventilation	Power	55	W

Universal Motors S.A.
 Rua Comendador Brandão, 484
 4495-375 Póvoa de Varzim
geral@universalmotors.pt
 TEL.: 252 299 080

Universal Motors UK, Ltd
 Unit E2, Meltham Mills Road
 West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
 TEL.: +44(0) 1484660222

Universal Motors SL
 C/La Habana n.6 nave 4 PI Camporoso
 28806 Alcala de Henares
info@universalmotors-group.es
 TEL.: 918 864 213