


Technical Data Sheet
Electric Motor Three phase in Aluminum IE1



L (standard motor)

217

L (motor w/brake)

290

L (motor w/forced ventilation)

310

L (motor without ventilation)

185

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
63	100	80	40	7	11j6	23	4	8.5	12.5	M4x10	126	100	122	183	-	-	-	-	-

Electrical Data

Type	UM1A 63M1-6	
Poles	6/1000	Poles
Power	0.09	Kw
Voltage	400	V
Frequency	50	Hz
Speed	870	rpm
Nominal current	0.40	A
Power factor	0.63	
Efficiency 100%	51.1	%
Efficiency 75%	49.2	%
Efficiency 50%	42.5	%
Torque	0.99	N.m
Ta/Tn	1.8	
Ia/In	2.6	
Tm/Tn	2	

Mechanical Data

Shaft height	63
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	50 dB(A)
Weight	4.2 kg
Bearing DE	6201 2Z C3
Bearing NDE	6201 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-06	Brake torque	4	N.m
AC brake	AC1	Brake torque	4.5	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	25	W
Three-phase forced ventilation	Power	25	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213