



L (standard motor)

217

L (motor w/brake)

290

L (motor w/forced ventilation)

310

L (motor without ventilation)

185

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
63	100	80	40	7	11j6	23	4	8.5	12.5	M4x10	126	100	122	183	-	-	-	-	-

Electrical Data

Type	UM2A 63M3-4	
Poles	4/1500	Poles
Power	0.25	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1385	rpm
Nominal current	0.79	A
Power factor	0.67	
Efficiency 100%	68.5	%
Efficiency 75%	67.7	%
Efficiency 50%	62.7	%
Torque	1.72	N.m
Ta/Tn	2.1	
Ia/In	4.0	
Tm/Tn	2.3	

Mechanical Data

Shaft height	63
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	54 dB(A)
Weight	5.4 kg
Bearing DE	6201 2Z C3
Bearing NDE	6201 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-06	Brake torque	4	N.m
AC brake	AC1	Brake torque	4.5	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	25	W
Three-phase forced ventilation	Power	25	W