

Technical Data Sheet
Electric Motor Three phase in Aluminum -



L (standard motor)

245

L (motor w/brake)

300

L (motor w/forced ventilation)

350

L (motor without ventilation)

212

Feet					Shaft							Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T	
71	112	90	45	7	14j6	30	5	11	16	M5x12	142	110	138	198	-	-	-	-	-	

Electrical Data

Type	UMDA 71M-4/6	
Poles	4/6	Poles
Power	0,22 / 0,15	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1400 / 910	rpm
Nominal current	0,81 / 0,64	A
Power factor	0,71 / 0,68	
Efficiency 100%	55 / 50	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	1,5 / 1,57	N.m
Ta/Tn	1,8 / 1,9	
Ia/In	3,5 / 3,2	
Tm/Tn	1,9 / 2,0	

Mechanical Data

Shaft height	71
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	- dB(A)
Weight	6.2 kg
Bearing DE	6202 2Z C3
Bearing NDE	6202 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-06	Brake torque	4	N.m
AC brake	AC2	Brake torque	10	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	35	W
Three-phase forced ventilation	Power	35	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213