

Technical Data Sheet
Electric Motor Three phase in Aluminum IE2



L (standard motor)

285

L (motor w/brake)

345

L (motor w/forced ventilation)

392

L (motor without ventilation)

242

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
80	125	100	50	10	19j6	40	6	15.5	21.5	M6x16	162	127	158	228	-	-	-	-	-

Electrical Data

Type	UM2A 80M2-4	
Poles	4/1500	Poles
Power	0.75	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1420	rpm
Nominal current	1.92	A
Power factor	0.71	
Efficiency 100%	79.6	%
Efficiency 75%	79.8	%
Efficiency 50%	77.1	%
Torque	5.04	N.m
Ta/Tn	2.7	
Ia/In	5.7	
Tm/Tn	2.9	

Mechanical Data

Shaft height	80
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	58 dB(A)
Weight	10.4 kg
Bearing DE	6204 2Z C3
Bearing NDE	6204 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-08	Brake torque	8	N.m
AC brake	AC3	Brake torque	16	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	45	W
Three-phase forced ventilation	Power	45	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213