

Technical Data Sheet
Electric Motor Three phase in Aluminum IE4



L (standard motor)

345

L (motor w/brake)

390

L (motor w/forced ventilation)

447

L (motor without ventilation)

290

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
90	140	125	56	10	24j6	50	8	20	27	M8x19	180	157	176	245	-	-	-	-	-

Electrical Data

Type	UM4A 90L-4	
Poles	4/1500	Poles
Power	1.50	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1455	rpm
Nominal current	3.46	A
Power factor	0.71	
Efficiency 100%	88.2	%
Efficiency 75%	88.1	%
Efficiency 50%	86.1	%
Torque	9.84	N.m
Ta/Tn	4.8	
Ia/In	9.2	
Tm/Tn	3.8	

Mechanical Data

Shaft height	90	
Construction form	B3	
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	61	dB(A)
Weight	21.5	kg
Bearing DE	6205 2Z C3	
Bearing NDE	6205 2Z C3	

Extra Data

Applicable brakes

DC brake	REB-05-10	Brake torque	16	N.m
AC brake	AC4	Brake torque	20	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	45	W
Three-phase forced ventilation	Power	45	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213