


Technical Data Sheet
Electric Motor Three phase in Aluminum -



L (standard motor)

345

L (motor w/brake)

390

L (motor w/forced ventilation)

447

L (motor without ventilation)

290

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
90	140	125	56	10	24j6	50	8	20	27	M8x19	180	157	176	245	-	-	-	-	-

Electrical Data

Type	UMDA 90L-2/4	
Poles	2/4	Poles
Power	1,7 / 1,32	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2830 / 1400	rpm
Nominal current	3,91 / 3,28	A
Power factor	0,86 / 0,83	
Efficiency 100%	73 / 70	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	5,74 / 9	N.m
Ta/Tn	2,0 / 2,0	
Ia/In	5,0 / 5,0	
Tm/Tn	2,0 / 2,0	

Mechanical Data

Shaft height	90
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	- dB(A)
Weight	14.6 kg
Bearing DE	6205 2Z C3
Bearing NDE	6205 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-10	Brake torque	16	N.m
AC brake	AC4	Brake torque	20	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	45	W
Three-phase forced ventilation	Power	45	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213