

Technical Data Sheet

Electric Motor Three phase in Aluminum -



L (standard motor)

380

L (motor w/brake)

450

L (motor w/forced ventilation)

485

L (motor without ventilation)

328

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
100	160	140	63	12	28j6	60	8	24	31	M10x22	205	183	199	267	-	-	-	-	-

Electrical Data

Type	UMDA 100L2-4/6	
Poles	4/6	Poles
Power	1,76 / 1,2	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1430 / 950	rpm
Nominal current	4,04 / 3,3	A
Power factor	0,85 / 0,75	
Efficiency 100%	74 / 70	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	11,75 / 12,06	N.m
Ta/Tn	1,8 / 1,8	
Ia/In	5,0 / 4,5	
Tm/Tn	2,0 / 2,0	

Mechanical Data

Shaft height	100
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S1
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	- dB(A)
Weight	24.7 kg
Bearing DE	6206 2Z C3
Bearing NDE	6206 2Z C3

Extra Data

Applicable brakes

DC brake	REB-05-12	Brake torque	32	N.m
AC brake	AC5	Brake torque	40	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	65	W
Three-phase forced ventilation	Power	65	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213