


Technical Data Sheet  
Electric Motor Three phase in Aluminum -



L (standard motor)

655

L (motor w/brake)

735

L (motor w/forced ventilation)

765

L (motor without ventilation)

560

| Feet |   |   |   |   | Shaft |     |    |    |    |        | Carcass |    |     |     | Flange |     |     |    |   |
|------|---|---|---|---|-------|-----|----|----|----|--------|---------|----|-----|-----|--------|-----|-----|----|---|
| H    | A | B | C | K | D     | E   | F  | G  | GA | X      | AB      | BB | AC  | HD  | M      | N   | P   | S  | T |
| -    | - | - | - | - | 42k6  | 110 | 12 | 37 | 45 | M16x36 | -       | -  | 314 | 231 | 300    | 250 | 350 | 19 | 5 |

### Electrical Data

|                 |               |       |
|-----------------|---------------|-------|
| Type            | UMDA 160L-4/8 |       |
| Poles           | 4/8           | Poles |
| Power           | 10/6,5        | Kw    |
| Voltage         | 400           | V     |
| Frequency       | 50            | Hz    |
| Speed           | 1450 / 725    | rpm   |
| Nominal current | 18,77 / 18,47 | A     |
| Power factor    | 0,88 / 0,68   |       |
| Efficiency 100% | 84 / 82       | %     |
| Efficiency 75%  | -             | %     |
| Efficiency 50%  | -             | %     |
| Torque          | 65,86 / 93,5  | N.m   |
| Ta/Tn           | 1,8 / 1,9     |       |
| Ia/In           | 5,5 / 5,0     |       |
| Tm/Tn           | 2,3 / 2,1     |       |

### Mechanical Data

|                       |            |
|-----------------------|------------|
| Shaft height          | -          |
| Construction form     | B5         |
| Mechanical protection | 55         |
| Heating class         | B          |
| Insulation class      | F          |
| Service               | S1         |
| Ambient temp.         | -10°C-40°C |
| Altitude              | 1000       |
| Noise                 | - dB(A)    |
| Weight                | 88 kg      |
| Bearing DE            | 6309 2Z C3 |
| Bearing NDE           | 6209 2Z C3 |

### Extra Data

#### Applicable brakes

|          |     |              |     |     |
|----------|-----|--------------|-----|-----|
| DC brake | K8  | Brake torque | 200 | N.m |
| AC brake | AC8 | Brake torque | 200 | N.m |

#### Applicable forced ventilations

|                                 |       |    |   |
|---------------------------------|-------|----|---|
| Single-phase forced ventilation | Power | NA | W |
| Three-phase forced ventilation  | Power | 60 | W |

Universal Motors S.A.  
Rua Comendador Brandão, 484  
4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
TEL.: 252 299 080

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Road  
West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
TEL.: +44(0) 1484660222

Universal Motors SL  
C/La Habana n.6 nave 4 PI Camporoso  
28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
TEL.: 918 864 213