


Technical Data Sheet

Electric Motor Three phase in Cast Iron IE1



L (standard motor)

1335

L (motor w/brake)

NA

L (motor w/forced ventilation)

1515

L (motor without ventilation)

1160

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T
315	508	457	216	28	80m6	170	22	71	85	M20x42	635	680	620	845	-	-	-	-	-

Electrical Data

Type	EM30 315M-4
Poles	4/1500 Poles
Power	132.00 Kw
Voltage	400 V
Frequency	50 Hz
Speed	1480 rpm
Nominal current	228.40 A
Power factor	0.88
Efficiency 100%	94.8 %
Efficiency 75%	- %
Efficiency 50%	- %
Torque	851.6900000000001N.m
Ta/Tn	2.1
Ia/In	6.9
Tm/Tn	2.2

Mechanical Data

Shaft height	315
Construction form	B3
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	93 dB(A)
Weight	940 kg
Bearing DE	NU 319
Bearing NDE	6319 C3

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	450	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213