

Technical Data Sheet
Electric Motor Three phase in Cast Iron IE1



L (standard motor)

-

L (motor w/brake)

-

L (motor w/forced ventilation)

-

L (motor without ventilation)

-

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T

Electrical Data

Type	EM30 355M-2	
Poles	2/3000	Poles
Power	250.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2980	rpm
Nominal current	412.00	A
Power factor	0.92	
Efficiency 100%	95.2	%
Efficiency 75%	-	%
Efficiency 50%	-	%
Torque	801.12	N.m
Ta/Tn	1.6	
Ia/In	7.1	
Tm/Tn	2.2	

Mechanical Data

Shaft height		
Construction form		
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S3-70%	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	103	dB(A)
Weight	1685	kg
Bearing DE		
Bearing NDE		

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	700	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213