

Technical Data Sheet  
Gearbox  
HELLICAL BEVEL




|                    |            |
|--------------------|------------|
| MODEL              | X33S       |
| Ø OUTPUT SHAFT     | 20 mm      |
| APPROXIMATE RATIO  | 80         |
| EXACT RATIO        | 79.64      |
| OUTPUT SPEED       | 18 RPM     |
| EXACT OUTPUT SPEED | 18 RPM     |
| INPUT POWER        | 0.09 KW    |
| INPUT ROTATION     | 1400 RPM   |
| INPUT PAM          | 56B14      |
| OUTPUT TORQUE      | 45.96 N.m  |
| NOMINAL TORQUE     | 100.00 N.m |
| NOMINAL POWER      | 0.2 KW     |
| SERVICE FACTOR     | 2.22       |
| DYNAMIC EFFICIENCY | 0.94       |

#### Oil Quantity (L)

| B3/H1 | B6/H4 | B7/H3 | B8/H2 | V5/H5 | V6/H6 |
|-------|-------|-------|-------|-------|-------|
| 0.7   | 0.65  | 0.4   | 0.65  | 0.95  | 0.65  |

#### Radial and Axial Loads



| $n_2$ [min-1] | FA [N] | FR [N] |
|---------------|--------|--------|
| 250           | 400    | 2000   |
| 100           | 500    | 2500   |
| 50            | 560    | 2800   |
| 15            | 560    | 2800   |

Universal Motors S.A.  
Rua Comendador Brandão, 484  
4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
TEL.: 252 299 080

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Road  
West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
TEL.: +44(0) 1484660222

Universal Motors SL  
C/La Habana n.6 nave 4 PI Camporoso  
28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
TEL.: 918 864 213





**P**X33SC...

Basic Gearbox  
Riduttore base

**Gearbox weight**  
peso riduttore


**6.55 kg**

| M. flanges   | Kit code   | $\phi F$ | A     |
|--------------|------------|----------|-------|
| <b>63B5</b>  | K050.4.041 | 138      | 189.5 |
| <b>71B5</b>  | K050.4.042 | 160      | 187   |
|              |            |          |       |
| <b>56B14</b> | KC40.4.049 | 80       | 187   |
| <b>63B14</b> | K050.4.047 | 90       | 189.5 |
| <b>71B14</b> | K050.4.045 | 105      | 187   |



### Standard

Hollow shaft




**On request**  
A richiesta

4 holes M8x15

**Mounting holes  
position**


**Posizione fori di montaggio**

## PX33S...FB..

Feet  
Piedini


PX33S...**-F1**.. Output flange  
Flangia uscita

Flangia uscita




PX33S...**-F2..** Output flange  
Flangia uscita

Flangia uscita




|                       |                                     |
|-----------------------|-------------------------------------|
| PX33S... <b>BR</b> .. | Reaction Arm<br>Braccio di reazione |
|-----------------------|-------------------------------------|

- Braccio di reazione


**RX33S...**

Input shaft  
Albero in entrata



PX33S**A**.. Single output shaft  
Albero semplice in uscita

Single output shaft  
Albero semplice in uscita



| d1                               | b1 | c1   | e1   | m1    | n1  | t2   | o1    | ① kit code |
|----------------------------------|----|------|------|-------|-----|------|-------|------------|
| ø20 k6                           | 6  | 37.5 | 40   | 120   | 160 | 22.5 | M8x20 | KX2S.5.028 |
| ø25 <sup>-0.005<br/>-0.020</sup> | 8  | 60   | 63.2 | 126.8 | 190 | 28   | M8x20 | K063.5.028 |