

MODEL	X53A
Ø OUTPUT SHAFT	30 mm
APPROXIMATE RATIO	66
EXACT RATIO	65.79
OUTPUT SPEED	22 RPM
EXACT OUTPUT SPEED	22 RPM
INPUT POWER	0.55 KW
INPUT ROTATION	1400 RPM
INPUT PAM	80B14
OUTPUT TORQUE	232.00 N.m
NOMINAL TORQUE	250.00 N.m
NOMINAL POWER	0.59 KW
SERVICE FACTOR	1.07
DYNAMIC EFFICIENCY	0.94

Oil Quantity (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
1.3	1.55	0.85	1.45	2.1	1.25








Radial and Axial Loads



n_2 [min-1]	F_A [N]	F_R [N]
250	600	3000
100	800	4000
50	960	4800
15	1660	8300

PX53AC...Basic Gearbox
Riduttore baseGearbox
weight
peso riduttore **12.65 kg**

M. flanges	Kit code	øF	A
63B5	K063.4.041	140	246
71B5	K063.4.042	160	244
80/90B5	K063.4.043	200	246
71B14	K063.4.047	105	244
80B14	K063.4.046	120	246
90B14	K063.4.041	140	246

**PX53A...FB..** Feet
Piedini**PX53A...-F2..** Output flange
Flangia uscita**PX53A...-F3..** Output flange
Flangia uscita**PX53A...-F4..** Output flange
Flangia uscita**RX53A...** Input shaft
Albero in entrata**PX53A...BR..** Reaction Arm
Braccio di reazione**PX53AA..** Single output shaft
Albero semplice in uscita