

Technical Data Sheet
Gearbox
SHAFT MOUNTED



MODEL	FA53	
Ø OUTPUT SHAFT	35	mm
APPROXIMATE RATIO	62	
EXACT RATIO	61.89	
OUTPUT SPEED	24	RPM
EXACT OUTPUT SPEED	24	RPM
INPUT POWER	1.50	KW
INPUT ROTATION	1400	RPM
INPUT PAM	90B5	
OUTPUT TORQUE	595.23	N.m
NOMINAL TORQUE	510.00	N.m
NOMINAL POWER	1.3	KW
SERVICE FACTOR	0.87	
DYNAMIC EFFICIENCY	0.94	



Oil Quantity (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
2.15	1.25	1.25	1.45	2.35	1.45

Radial and Axial Loads



n_2 [min-1]	FA [N]	FR [N]
300	400	2000
200	440	2200
120	500	2500
15	1140	5700

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporosso
28806 Alcalá de Henares
info@universalmotors-group.es
TEL.: 918 864 213

Gearbox weight peso riduttore	15.5 kg
---	----------------

Technical drawing of the KF60.0.210LM kit, showing side and front views with dimensions.

Side View Dimensions:

- Overall width: 173
- Distance from left edge to centerline: 6.5
- Distance from centerline to right edge: 92

Front View Dimensions:

- Overall width: 157.5
- Distance from left edge to centerline: 30
- Distance from centerline to right edge: 30
- Overall height: $\varnothing 35\ H7$