

Technical Data Sheet  
Gearbox  
INLINE GEARBOX



|                    |            |
|--------------------|------------|
| MODEL              | 413A       |
| Ø OUTPUT SHAFT     | 25 mm      |
| APPROXIMATE RATIO  | 97         |
| EXACT RATIO        | 96.85      |
| OUTPUT SPEED       | 15 RPM     |
| EXACT OUTPUT SPEED | 15 RPM     |
| INPUT POWER        | 0.09 KW    |
| INPUT ROTATION     | 1400 RPM   |
| INPUT PAM          | 56B14      |
| OUTPUT TORQUE      | 55.89 N.m  |
| NOMINAL TORQUE     | 160.00 N.m |
| NOMINAL POWER      | 0.26 KW    |
| SERVICE FACTOR     | 2.89       |
| DYNAMIC EFFICIENCY | 0.94       |

Oil Quantity (L)

| B3/H1 | B6/H4 | B7/H3 | B8/H2 | V5/H5 | V6/H6 |
|-------|-------|-------|-------|-------|-------|
| 0.3   | 0.35  | 0.45  | 0.45  | 0.45  | 0.55  |

Radial and Axial Loads




| $n_2$ [min-1] | FA [N] | FR [N] |
|---------------|--------|--------|
| 300           | 310    | 1550   |
| 200           | 360    | 1800   |
| 120           | 448    | 2240   |
| 70            | 540    | 2700   |

Universal Motors S.A.  
Rua Comendador Brandão, 484  
4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
TEL.: 252 299 080

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Road  
West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
TEL.: +44(0) 1484660222

Universal Motors SL  
C/La Habana n.6 nave 4 PI Camporoso  
28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
TEL.: 918 864 213

P413A **B1** ...  
With feet  
Con piediniGearbox  
weight  
peso riduttore With flange **6.1 kg**  
With feet **6.3 Kg**


Feet / piedini

| Feet Code | Market reference | G  | H   | R       | L      | L1 | S   | H1    | O  | Øl | S2 only with motor flange | B5 max. Flange | kit code   |
|-----------|------------------|----|-----|---------|--------|----|-----|-------|----|----|---------------------------|----------------|------------|
| B1        | 112              | 18 | 85  | 110     | 87     | 50 | 130 | 167.5 | 15 | -  | -                         | -              | KC35.9.021 |
| B2        | 212/3            | 18 | 100 | 130     | 107.5  | 60 | 155 | 182.5 | 17 | 11 | -                         | -              | KC40.9.025 |
| S1        | 17               | 18 | 75  | 110     | 90÷110 | 50 | 145 | 155.5 | 15 | 9  | 2 80/90B5                 | -              | KC40.9.022 |
| S2        | 27               | 25 | 90  | 110     | 130    | -  | 145 | 172.5 | 20 | 9  | -                         | -              | KC40.9.024 |
| H2        | 022-223          | 25 | 100 | 110     | 115    | -  | 145 | 182.5 | 20 | 9  | -                         | -              | KC40.9.026 |
| M1        | 42/3             | 25 | 80  | 110÷120 | 85     | -  | 145 | 162.5 | 15 | 9  | -                         | -              | KC40.9.023 |

Other feet are available, see our web site  
Sono disponibili altri piedini, consulta il nostro sito web

A see on page bottom

Most popular types  
Tipi più diffusi

P413A-**F** ...  
Output flanges  
flange di uscita


\*Available output shaft / Albero di uscita

|                           | Shaft - d1 | p1 | h1   | x     |
|---------------------------|------------|----|------|-------|
| Standard                  | Ø 25x50    | 8  | 28   | M8x19 |
| On request<br>A richiesta | Ø 16x40    | 5  | 18   | M6x16 |
|                           | Ø 19x40    | 6  | 21.5 | M6x16 |
|                           | Ø 20x40    | 6  | 22.5 | M8x19 |
|                           | Ø 24x50    | 8  | 27   | M8x19 |


Available output flanges / flange di uscita

| a1 Ø | b1  | c1   | e1  | f1  | s1 | kit code   |
|------|-----|------|-----|-----|----|------------|
| 120  | 80  | 10   | 100 | 3   | 7  | KC40.9.010 |
| 140  | 95  | 10   | 115 | 3   | 9  | KC40.9.011 |
| 160  | 110 | 10   | 130 | 3.5 | 9  | KC40.9.012 |
| 200  | 130 | 10   | 165 | 3.5 | 11 | KC40.9.013 |
| 250  | 180 | 11.5 | 215 | 3.5 | 14 | KC40.9.014 |

With flange and feet only on request.  
Ask for compatibility

P413A-**N** ...  
Basic gearbox  
Riduttore baseSuggested B14  
motor flanges

| B5 Motor Flanges | A     | C <sub>max</sub> | g6  | k1    | kit code   |
|------------------|-------|------------------|-----|-------|------------|
| 63 B5            | 185.5 | 173.2            | 140 | 189.5 | K050.4.041 |
| 71 B5            | 183   | 183.2            | 160 | 187   | K050.4.042 |

R413A-**N** ...  
Input Shaft  
Albero in entrata

| B14 Motor Flanges | A     | C <sub>max</sub> | g6  | k1    | kit code   |
|-------------------|-------|------------------|-----|-------|------------|
| 56 B14            | 183   | 143.2            | 80  | 187   | KC40.4.049 |
| 63 B14            | 185.5 | 148.2            | 90  | 189.5 | K050.4.047 |
| 71 B14            | 183   | 155.7            | 105 | 187   | K050.4.045 |