

Technical Data Sheet
Gearbox
INLINE GEARBOX



MODEL	513A
Ø OUTPUT SHAFT	30 mm
APPROXIMATE RATIO	180
EXACT RATIO	180.40
OUTPUT SPEED	8 RPM
EXACT OUTPUT SPEED	8 RPM
INPUT POWER	0.25 KW
INPUT ROTATION	1400 RPM
INPUT PAM	71B14
OUTPUT TORQUE	289.17 N.m
NOMINAL TORQUE	354.00 N.m
NOMINAL POWER	0.31 KW
SERVICE FACTOR	1.24
DYNAMIC EFFICIENCY	0.94

Oil Quantity (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
1	0.9	1.65	1.15	1.45	1.4

Radial and Axial Loads




n_2 [min-1]	FA [N]	FR [N]
300	460	2300
200	520	2600
120	620	3100
15	1000	5000

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213

Gearbox weight peso riduttore	With flange	11.9 kg
	With feet	12.1 Kg



Feet Code	Market reference	G	H	R	L	S	H1	O	øI	S2 only with motor flange	B5 max. Flange	kit code
B3	312/3	18	110	160	130	190	211	20	11	-	-	KC50.9.024
B4	30/35	20	130	180	149.5	216	231	18	14	-	-	KC60.9.024
S4	47-57	30	115	135	165	170	216	25	14	-	-	KC50.9.022
H3	023-233	30	130	135	135	185	231	25	14	-	-	KC50.9.025
M2	52/3	30	110	135-150	100	190	211	18	11	-	-	KC50.9.023

 Most popular types
Tipi più diffusi

flange di uscita

Technical drawing of the output shaft assembly. The drawing includes a front view on the left showing a circular shaft with a central hole of diameter d_1 and a mounting flange with diameter p_1 . A side view on the right shows the shaft with dimensions a_1 , b_1 , r_1 , f_1 , c_1 , 57.5 , 15 , g_6 , and k_1 . A circular detail view labeled 'Detail Y' shows a cross-section of the shaft with dimensions 8.5 with KC50.9.011, 2.5 , and h_1 . The shaft is labeled 'x'.

Available output shaft / Albero di uscita

	Shaft - d1	p1	h1	x
Standard	ø 30x60	8	33	M10x22
On request A richiesta	ø 24x50	8	27	M8x19
	ø 25x50	8	28	M8x19
	ø 28x60	8	31	M8x19
	ø 35x60	10	38	M10x22

a1 ø	b1	c1	e1	f1	s1	kit code
160	110	14	130	3.5	11	KC50.9.011
200	130	13	165	3.5	11	KC50.9.012
250	180	15.5	215	4	14	KC50.9.013

With flange and feet only on request.
Ask for compatibility

Technical drawing of the B14 motor flange, showing side and top views with dimensions.

Side View Dimensions:


- Overall length: 217.5
- Flange thickness: 9.6
- Flange diameter: $\phi 123$
- Motor flange diameter: $\phi 30$
- Motor flange length: 15.5
- Motor flange offset: 5
- Motor flange offset: 50
- Motor flange offset: 15
- Motor flange offset: 60
- Motor flange offset: 12
- Motor flange offset: 33
- Motor flange offset: ∞
- Motor flange offset: M10x22
- Motor flange offset: h6

Top View Dimensions:

- Overall diameter: $\phi 123$
- Flange thickness: 9.6
- Motor flange diameter: $\phi 30$
- Motor flange length: 15.5
- Motor flange offset: 5
- Motor flange offset: 50
- Motor flange offset: 15
- Motor flange offset: 60
- Motor flange offset: 12
- Motor flange offset: 33
- Motor flange offset: ∞
- Motor flange offset: M10x22
- Motor flange offset: h6

Notes:

- Suggested B14 motor flanges
- N.5 M10x17
- 65°
- 50°
- 69.5
- 170.5



B14 Motor Flanges	A	C_{max}	g6	k1	kit code	k1 with KC50.9.011
71 B14	236	197.5	105	238.5	K063.4.047	244.5
80 B14	238	205	120	240.5	K063.4.046	246.5
90 B14	238	215	140	240.5	K063.4.041	246.5