



MODEL	UMSG50	
Ø OUTPUT SHAFT	25	mm
APPROXIMATE RATIO	7.5	
EXACT RATIO	7.50	
OUTPUT SPEED	195	RPM
EXACT OUTPUT SPEED	195	RPM
INPUT POWER	0.55	KW
INPUT ROTATION	1400	RPM
INPUT PAM	80B14	
OUTPUT TORQUE	24.76	N.m
NOMINAL TORQUE	72.03	N.m
NOMINAL POWER	1.6	KW
SERVICE FACTOR	2.91	
DYNAMIC EFFICIENCY	0.88	



Oil Quantity (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
0.15	0.15	0.15	0.15	0.15	0.15

Radial and Axial Loads



n_2 [min-1]	FA [N]	FR [N]
200	240	1200
100	300	1500
50	380	1900
15	560	2800



Square flange FA



Square flange FB




Feet



Reaction arm



Single Shaft



b1	c1	d1	e1	m1	n1	t2	o1
8	50	25	53.5	92	153	28	M10

1400 rpm	N2	Relação	P1	FS	P1n	M2	Rend.	Fr max	Veio		Flanges de entrada				
	rpm	i	kW		kW	Nm	%	N	Entrada	Saída	63	71	80		
UMSG50	187	7,5	1,1	1,5	1,6	71	0,88	1805	19	25		B14/B5	B14/B5		
	140	10	1,1	1,1	1,2	70	0,86	1987				B14/B5	B14/B5		
	93	15	0,75	1,2	0,88	73	0,82	2274				B14/B5	B14/B5		
	70	20	0,75	0,9	0,68	72	0,79	2503				B14/B5	B14/B5		
	56	25	0,55	1,0	0,54	69	0,76	2696				B14/B5	B14/B5		
	47	30	0,55	1,0	0,57	83	0,72	2865				B14/B5	B14/B5		
	35	40	0,37	1,1	0,42	77	0,67	3153	14			B14/B5			
	28	50	0,37	0,9	0,34	73	0,63	3397				B14/B5	B14/B5		
	23	60	0,25	1,1	0,28	68	0,59	3610				B14/B5	B14/B5		
	18	80	0,25	0,9	0,22	64	0,53	3973				B14/B5	B14/B5		
	14	100	0,18	1,0	0,18	52	0,49	4280			11		B14/B5		