

MODEL	UMSG75	
Ø OUTPUT SHAFT	28	mm
APPROXIMATE RATIO	10	
EXACT RATIO	10.00	
OUTPUT SPEED	146	RPM
EXACT OUTPUT SPEED	146	RPM
INPUT POWER	2.20	KW
INPUT ROTATION	1400	RPM
INPUT PAM	100B5	
OUTPUT TORQUE	132.05	N.m
NOMINAL TORQUE	192.08	N.m
NOMINAL POWER	3.2	KW
SERVICE FACTOR	1.45	
DYNAMIC EFFICIENCY	0.88	



Oil Quantity (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
0.5	0.5	0.5	0.5	0.5	0.5

Radial and Axial Loads



n_2 [min ⁻¹]	FA [N]	FR [N]
200	460	2300
100	560	2800
50	720	3600
15	1000	5000



Square flange FA



Round flange FB



Feet



Reaction arm



Single Shaft



b1	c1	d1	e1	m1	n1	t2	$\phi 1$
8	60	28	63.5	120	192	31	M10

1400 rpm	N2	Relação	P1	FS	P1n	M2	Rend.	Fr max	Veio		Flanges de entrada				
	rpm	i	kW		kW	Nm	%	N	Entrada	Saída	71	80	90	100/112	
UMSG75	187	7,5	4	1,0	4,1	185	0,89	2785	28	28			B14/B5	B14/B5	
	140	10	3	1,1	3,2	190	0,88	3065				B14/B5	B14/B5		
	93	15	2,2	1,0	2,3	198	0,85	3509				B14/B5	B14/B5		
	70	20	1,5	1,3	1,9	210	0,82	3862			B14/B5	B14/B5			
	56	25	1,5	1,0	1,5	202	0,8	4160			B14/B5	B14/B5			
	47	30	1,5	1,0	1,5	233	0,76	4421			B14/B5	B14/B5			
	35	40	1,1	1,0	1,1	216	0,72	4865			B14/B5	B14/B5			
	28	50	0,75	1,2	0,89	206	0,69	5241			B5	B14/B5			
	23	60	0,75	1,0	0,75	197	0,65	5569	19			B5	B14/B5		
	18	80	0,55	1,1	0,58	197	0,6	6130				B5	B14/B5		
	14	100	0,37	1,3	0,48	180	0,55	6603			14		B5	B14/B5	