

Technical Data Sheet
Electric Motor Three phase in Aluminum IE3



L (standard motor)

-

L (motor w/brake)

-

L (motor w/forced ventilation)

-

L (motor without ventilation)

-

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T

Electrical Data

Type	PE31/UM3A* 80M-4	
Poles	4/1500	Poles
Power	0.75	Kw
Voltage	400	V
Frequency	50	Hz
Speed	1410	rpm
Nominal current	1.75	A
Power factor	0.75	
Efficiency 100%	82.5	%
Efficiency 75%	83.4	%
Efficiency 50%	82.8	%
Torque	5.08	N.m
Ta/Tn	2.3	
Ia/In	6.5	
Tm/Tn	2.3	

Mechanical Data

Shaft height		
Construction form		
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S1	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	71	dB(A)
Weight	12	kg
Bearing DE		
Bearing NDE		

Extra Data

Applicable brakes

DC brake	REB-05-08	Brake torque	8	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	45	W
Three-phase forced ventilation	Power	45	W

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213