

L (standard motor)

-

L (motor w/brake)

-

L (motor w/forced ventilation)

-

L (motor without ventilation)

-

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T

### Electrical Data

Type	HE30 250M-2	
Poles	2/3000	Poles
Power	55.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2970	rpm
Nominal current	95.70	A
Power factor	0.89	
Efficiency 100%	93.2	%
Efficiency 75%	93.9	%
Efficiency 50%	92.8	%
Torque	176.8	N.m
Ta/Tn	2.2	
Ia/In	7.6	
Tm/Tn	2.3	

### Mechanical Data

Shaft height	
Construction form	
Mechanical protection	55
Heating class	B
Insulation class	F
Service	S3-70%
Ambient temp.	-10°C-40°C
Altitude	1000
Noise	89 dB(A)
Weight	387 kg
Bearing DE	
Bearing NDE	

### Extra Data

#### Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

#### Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	200	W