Technical Data Sheet
Electric Motor Three phase in Cast Iron IE2

L (standard motor)
-

L (motor w/brake)
-

L (motor w/forced ventilation)
-

L (motor without ventilation)
-

| Feet | | | | | Shaft | | | | | | Carcass | | | | Flange | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| H | A | B | C | K | D | E | F | G | GA | X | AB | BB | AC | HD | M | N | P | S | T |
| | | | | | | | | | | | | | | | | | | | |

## Electrical Data

| | | |
|---|---|---|
| Type | HE30 280S-2 | |
| Poles | 2/3000 | Poles |
| Power | 75.00 | Kw |
| Voltage | 400 | V |
| Frequency | 50 | Hz |
| Speed | 2975 | rpm |
| Nominal current | 129.70 | A |
| Power factor | 0.89 | |
| Efficiency 100% | 93.8 | % |
| Efficiency 75% | 94.3 | % |
| Efficiency 50% | 93.1 | % |
| Torque | 240.7 | N.m |
| Ta/Tn | 2 | |
| Ia/In | 6.9 | |
| Tm/Tn | 2.3 | |

## Mechanical Data

| | | |
|---|---|---|
| Shaft height | | |
| Construction form | | |
| Mechanical protection | 55 | |
| Heating class | B | |
| Insulation class | F | |
| Service | S3-70% | |
| Ambient temp. | -10ºC-40ºC | |
| Altitude | 1000 | |
| Noise | 91 | dB(A) |
| Weight | 520 | kg |
| Bearing DE | | |
| Bearing NDE | | |

## Extra Data

**Applicable brakes**

| | | | | |
|---|---|---|---|---|
| DC brake | NA | Brake torque | NA | N.m |
| AC brake | NA | Brake torque | NA | N.m |

**Applicable forced ventilations**

| | | | |
|---|---|---|---|
| Single-phase forced ventilation | Power | NA | W |
| Three-phase forced ventilation | Power | 270 | W |

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 Pl Camporroso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213