

L (standard motor)

-

L (motor w/brake)

-

L (motor w/forced ventilation)

-

L (motor without ventilation)

-

Feet					Shaft						Carcass				Flange				
H	A	B	C	K	D	E	F	G	GA	X	AB	BB	AC	HD	M	N	P	S	T

Electrical Data

Type	PE30/UM3C*	
	315L2-2	
Poles	2/3000	Poles
Power	200.00	Kw
Voltage	400	V
Frequency	50	Hz
Speed	2980	rpm
Nominal current	331.13	A
Power factor	0.91	
Efficiency 100%	95.8	%
Efficiency 75%	95.9	%
Efficiency 50%	94.9	%
Torque	640.9	N.m
Ta/Tn	1.8	
Ia/In	7.2	
Tm/Tn	2.3	

Mechanical Data

Shaft height		
Construction form		
Mechanical protection	55	
Heating class	B	
Insulation class	F	
Service	S3-70%	
Ambient temp.	-10°C-40°C	
Altitude	1000	
Noise	92	dB(A)
Weight	1112	kg
Bearing DE		
Bearing NDE		

Extra Data

Applicable brakes

DC brake	NA	Brake torque	NA	N.m
AC brake	NA	Brake torque	NA	N.m

Applicable forced ventilations

Single-phase forced ventilation	Power	NA	W
Three-phase forced ventilation	Power	450	W