


Technical Data Sheet
Gearbox
WORM GEARBOX SQUARE DESIGN




MODEL	M13	
Ø OUTPUT SHAFT	45	mm
APPROXIMATE RATIO	80	
EXACT RATIO	80.00	
OUTPUT SPEED	18	RPM
EXACT OUTPUT SPEED	18	RPM
INPUT POWER	1.50	KW
INPUT ROTATION	1400	RPM
INPUT PAM	90B5	
OUTPUT TORQUE	556.59	N.m
NOMINAL TORQUE	853.00	N.m
NOMINAL POWER	2.3	KW
SERVICE FACTOR	1.53	
DYNAMIC EFFICIENCY	0.68	



Oil Quantity (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
4.5	3.5	3.5	3.3	4.5	3.3

Radial and Axial Loads



n_2 [min-1]	FA [N]	FR [N]
200	960	4800
100	1240	6200
50	1560	7800
15	2400	12000

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222


Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213

PM13FB...


Basic wormbox
Riduttore base

Gearbox weight peso riduttore	48.0 kg
---	----------------


M. flanges	Kit code	øF	A
90B5	KM13.4.041	200	180
100/112B5	KM13.4.042	250	180
132B5	KM13.4.043	300	180

PM13**FC**...

Square flange
Flangia quadrata




PM13FB...


Feet
Piedini

PM13BR...


Reaction arm
Braccio di reazione

PM13....**S**...

Single Shaft
Albero lento semplice

PM13....**D**...

Double Shaft
• Albero lento bisp.



① kit cod. KM13.5.028 type B

② kit cod. KM13.5.029 type B

[illegible]