

Ficha Técnica
Reductor de velocidad
EJES PARALELOS



MODELO	FA42	
Ø EJE DE SALIDA	30	mm
RELACIÓN APROXIMADA	8	
RELACIÓN EXACTA	8.38	
VELOCIDAD DE SALIDA	183	RPM
VELOCIDAD DE SALIDA EXACTA	174	RPM
POTENCIA DE ENTRADA	3.00	KW
ROTACIÓN DE ENTRADA	1400	RPM
PAM DE ENTRADA	100B14	
PAR DE SALIDA	164.62	N.m
PAR NOMINAL	225.00	N.m
POTENCIA NOMINAL	4.1	KW
FACTOR DE SERVICIO	1.37	
EFICIENCIA DINÁMICA	0.96	



Cantidad de Aceite (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
1.15	0.7	0.7	0.7	1.2	0.8

Cargas Radiales y Axiales



n_2 [min-1]	FA [N]	FR [N]
300	300	1500
200	350	1750
120	410	2050
15	800	4000

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporroso
28806 Alcalá de Henares
info@universalmotors-group.es
TEL.: 918 864 213

Gearbox weight peso riduttore	9.0 kg
---	---------------

On request
A richiesta

Technical drawing of the 1000 Series Motor Mounting Bracket. The drawing includes three views: a side view, a front view, and a detail view of the mounting hole.

Side View Dimensions:

- Overall width: A
- Top flange width: 40
- Top flange hole diameter: $\phi 11$
- Motor mounting flange diameter: ϕF
- Motor mounting flange height: 123
- Overall height: 269
- Height from base to top flange: 160
- Base hole diameter: $\phi 95 f7$
- Base hole offset from left: 3.5
- Base hole offset from right: 5
- Base width: 110

Front View Dimensions:

- Top flange width: 18
- Height from base to top flange: 88
- Base width: 115
- Overall width: 178
- 4 holes $M8 \times 15$

Detail View Dimensions:

- Mounting hole diameter: $\phi 15$
- Mounting hole offset from center: 25H7
- Mounting hole offset from edge: 8
- Overall width: 110

[illegible]