

Ficha Técnica
Reductor de velocidad
EJES PARALELOS



MODELO	FA53	
Ø EJE DE SALIDA	35	mm
RELACIÓN APROXIMADA	126	
RELACIÓN EXACTA	125.96	
VELOCIDAD DE SALIDA	12	RPM
VELOCIDAD DE SALIDA EXACTA	12	RPM
POTENCIA DE ENTRADA	0.55	KW
ROTACIÓN DE ENTRADA	1400	RPM
PAM DE ENTRADA	80B14	
PAR DE SALIDA	444.19	N.m
PAR NOMINAL	510.00	N.m
POTENCIA NOMINAL	0.63	KW
FACTOR DE SERVICIO	1.15	
EFICIENCIA DINÁMICA	0.94	



Cantidad de Aceite (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
2.15	1.25	1.25	1.45	2.35	1.45

Cargas Radiales y Axiales



n_2 [min-1]	FA [N]	FR [N]
300	400	2000
200	440	2200
120	500	2500
15	1140	5700

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporroso
28806 Alcalá de Henares
info@universalmotors-group.es
TEL.: 918 864 213

Gearbox weight peso riduttore	15.5 kg
---	----------------

Kit. Cod KF60.0.210LM

Technical drawing showing the dimensions of the Kit. Cod KF60.0.210LM. The drawing includes a side view and a front view.

Side View Dimensions:

- Overall width: 173
- Distance from left edge to centerline: 6.5
- Distance from centerline to right edge: 92

Front View Dimensions:

- Overall width: 157.5
- Distance from left edge to centerline: 30
- Distance from centerline to right edge: 30
- Overall height: $\varnothing 35$ H7
- Distance from bottom edge to centerline: 30
- Distance from centerline to top edge: 30