

MODELO	FA53	
Ø EJE DE SALIDA	35	mm
RELACIÓN APROXIMADA	326	
RELACIÓN EXACTA	325.97	
VELOCIDAD DE SALIDA	4	RPM
VELOCIDAD DE SALIDA EXACTA	4	RPM
POTENCIA DE ENTRADA	0.25	KW
ROTACIÓN DE ENTRADA	1400	RPM
PAM DE ENTRADA	71B14	
PAR DE SALIDA	522.50	N.m
PAR NOMINAL	510.00	N.m
POTENCIA NOMINAL	0.24	KW
FACTOR DE SERVICIO	0.96	
EFICIENCIA DINÁMICA	0.94	



Cantidad de Aceite (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
2.15	1.25	1.25	1.45	2.35	1.45

Cargas Radiales y Axiales



n_2 [min-1]	FA [N]	FR [N]
300	400	2000
200	440	2200
120	500	2500
15	1140	5700

Gearbox weight peso riduttore	15.5 kg
---	----------------

N°4 - s1

Kit. Cod KF60.0.210LM

Technical drawing showing the side view and cross-section of the KF60.0.210LM kit. The side view shows a main body with a width of 173 mm and a height of 92 mm. A small detail shows a square feature with a width of 6.5 mm. The cross-section view shows a cylindrical component with an outer diameter of $\varnothing 35$ H7 and a total length of 157.5 mm. The cross-section is divided into three parts: a central section of 30 mm and two outer sections of 30 mm each. The cross-section also shows a small detail of a square feature with a width of 6.5 mm.