

Ficha Técnica
Reductor de velocidad
EJES PARALELOS



MODELO	FA53	
Ø EJE DE SALIDA	35	mm
RELACIÓN APROXIMADA	280	
RELACIÓN EXACTA	279.22	
VELOCIDAD DE SALIDA	5	RPM
VELOCIDAD DE SALIDA EXACTA	5	RPM
POTENCIA DE ENTRADA	0.18	KW
ROTACIÓN DE ENTRADA	1400	RPM
PAM DE ENTRADA	63B5	
PAR DE SALIDA	322.25	N.m
PAR NOMINAL	510.00	N.m
POTENCIA NOMINAL	0.28	KW
FACTOR DE SERVICIO	1.56	
EFICIENCIA DINÁMICA	0.94	



Cantidad de Aceite (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
2.15	1.25	1.25	1.45	2.35	1.45

Cargas Radiales y Axiales



n_2 [min-1]	FA [N]	FR [N]
300	400	2000
200	440	2200
120	500	2500
15	1140	5700

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporroso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213

Gearbox weight peso riduttore	15.5 kg
---	----------------

Kit. Cod KF60.0.210LM

Technical drawing showing the side and front views of the KF60.0.210LM kit. The side view (top) shows a main body with a width of 173 mm and a height of 92 mm. A small protrusion on the left has a width of 6.5 mm. The front view (bottom) shows a cylindrical component with an outer diameter of $\varnothing 35$ H7 and a total length of 157.5 mm. The central section has a diameter of $\varnothing 25$ H7 and is divided into two 30 mm segments. A small feature on the right has a diameter of $\varnothing 10$ H7.