

MODELO	512A	
Ø EJE DE SALIDA	30	mm
RELACIÓN APROXIMADA	17	
RELACIÓN EXACTA	16.62	
VELOCIDAD DE SALIDA	86	RPM
VELOCIDAD DE SALIDA EXACTA	88	RPM
POTENCIA DE ENTRADA	2.20	KW
ROTACIÓN DE ENTRADA	1400	RPM
PAM DE ENTRADA	100B14	
PAR DE SALIDA	239.42	N.m
PAR NOMINAL	354.00	N.m
POTENCIA NOMINAL	3.3	KW
FACTOR DE SERVICIO	1.50	
EFICIENCIA DINÁMICA	0.96	

Cantidad de Aceite (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
0.7	0.8	1.15	1.2	1.15	1.25

Cargas Radiales y Axiales



n_2 [min-1]	F_A [N]	F_R [N]
300	460	2300
200	520	2600
120	620	3100
15	1000	5000

Gearbox weight peso riduttore	With flange	11.7 kg
	With feet	11.9 Kg



Feet Code	Market reference	G	H	R	L	S	H1	O	Øl	S2 only with motor flange	B5 max. Flange	kit code
B3	312/3	18	110	160	130	190	211	20	11	10 100/112B5 35 132B5	-	KC50.9.024
B4	30/35	20	130	180	149.5	216	231	18	14	15 132B5	-	KC60.9.024
S4	47-57	30	115	135	165	170	216	25	14	5 100/112B5 30 132B5	-	KC50.9.022
H3	023-233	30	130	135	135	185	231	25	14	15 132B5	-	KC50.9.025
M2	52/3	30	110	135-150	100	190	211	18	11	10 100/112B5 35 132B5	-	KC50.9.023

 Most popular types
Tipi più diffusi

Technical drawing of a wheel hub assembly. The drawing shows a cross-section of the hub with a central axle hole. Dimensions S_1 and S_2 are indicated. S_1 is the distance from the center of the axle hole to the center of one of the mounting holes. S_2 is the distance from the center of the axle hole to the outer edge of the hub.

	Shaft - d1	p1	h1	x
Standard	ø 30x60	8	33	M10x22
On request A richiesta	ø 24x50	8	27	M8x19
	ø 25x50	8	28	M8x19
	ø 28x60	8	31	M8x19
	ø 35x60	10	38	M10x22

a1 ø	b1	c1	e1	f1	s1	kit code
160	110	14	130	3.5	11	KC50.9.011
200	130	13	165	3.5	11	KC50.9.012
250	180	15.5	215	4	14	KC50.9.013

With flange and feet only on request.
Ask for compatibility

Technical drawing of the B14 motor flange assembly, showing side and top views with dimensions.

Side View Dimensions:

- Total width: 209
- Mounting flange diameter: $\varnothing 123$
- Central shaft diameter: $\varnothing 30$
- Mounting flange thickness: 6
- Central shaft length: 12
- Mounting flange inner diameter: 60
- Mounting flange outer diameter: 15.5
- Mounting flange inner diameter: 50
- Mounting flange outer diameter: 5.3
- Mounting flange inner diameter: 5
- Mounting flange outer diameter: 33
- Mounting flange inner diameter: 18
- Mounting flange outer diameter: 10

Top View Dimensions:

- Flange side length: 170.5
- Flange inner side length: 69.5
- Flange outer side length: 123
- Flange inner side length: 6.5
- Flange outer side length: 50°
- Flange inner side length: 65°
- Flange outer side length: 5.3
- Flange inner side length: 5
- Flange outer side length: 33
- Flange inner side length: 18
- Flange outer side length: 10

Labels:

- Suggested B14 motor flanges
- N.5 M10x17
- M10x22

[illegible]

B5 Motor Flanges	A	C_{max}	g6	k1	kit code	k1 with KC50.9.011	B14 Motor Flanges	A	C_{max}	g6	k1	kit code	k1 with KC50.9.011
71 B5	227.5	215.3	160	230	K023.4.041	236	80 B14	229.5	195.3	120	232	K085.4.046	238
80/90 B5	229.5	235.3	200	232	K023.4.042	238	90 B14	229.5	205.3	140	232	K085.4.045	238
100/112 B5	238.5	260.3	250	241	K023.4.043	247	100/112 B14	238.5	215.3	160	241	K085.4.047	247
132 B5	259.5	285.3	300	259	KC51.4.043	265	132 B14	259.5	235.3	200	259	KC51.4.041	265