


MODELO	UMSG40	
Ø EJE DE SALIDA	18	mm
RELACIÓN APROXIMADA	100	
RELACIÓN EXACTA	100.00	
VELOCIDAD DE SALIDA	15	RPM
VELOCIDAD DE SALIDA EXACTA	15	RPM
POTENCIA DE ENTRADA	0.12	KW
ROTACIÓN DE ENTRADA	1400	RPM
PAM DE ENTRADA	63B5	
PAR DE SALIDA	38.47	N.m
PAR NOMINAL	28.85	N.m
POTENCIA NOMINAL	0.09	KW
FACTOR DE SERVICIO	0.75	
EFICIENCIA DINÁMICA	0.47	




Cantidad de Aceite (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
0.1	0.1	0.1	0.1	0.1	0.1


Cargas Radiales y Axiales




n_2 [min-1]	FA [N]	FR [N]
200	180	900
100	220	1100
50	260	1400
15	400	2000




Square flange FA




Square flange FB




Feet



Reaction arm



Single Shaft



b1	c1	d1	e1	m1	n1	t2	o1
6	40	18	43	78	128	20.5	M6

1400 rpm	N2	Relação	P1	F5	P1n	M2	Rend.	Fr max	Veio		Flanges de entrada			
	rpm	i	kW		kW	Nm	%	N	Entrada	Saída	56	63	71	
UMSG40	187	7,5	0,55	1,6	0,9	40	0,87	1315	14	18		B14/B5	B14/B5	
	140	10	0,55	1,3	0,69	40	0,85	1447				B14/B5	B14/B5	
	93	15	0,55	0,9	0,48	39	0,82	1657				B14/B5	B14/B5	
	70	20	0,37	1,0	0,37	39	0,78	1824				B14/B5	B14/B5	
	56	25	0,25	1,2	0,3	38	0,75	1964				B14/B5	B14/B5	
	47	30	0,25	1,2	0,31	44	0,7	2087				B14/B5	B14/B5	
	35	40	0,25	0,9	0,23	41	0,65	2298				B14/B5	B14/B5	
	28	50	0,18	1,0	0,18	37	0,62	2475				B14/B5	B14/B5	
	23	60	0,12	1,3	0,15	35	0,58	2630	11			B14/B5	B14/B5	
	18	80	0,12	1,0	0,12	33	0,52	2895				B14/B5	B14/B5	
	14	100	0,09	1,0	0,09	29	0,47	3118				B14/B5	B14/B5	
												B14/B5	B14/B5	