


MODELO	UMSG50	
Ø EJE DE SALIDA	25	mm
RELACIÓN APROXIMADA	60	
RELACIÓN EXACTA	60.00	
VELOCIDAD DE SALIDA	24	RPM
VELOCIDAD DE SALIDA EXACTA	24	RPM
POTENCIA DE ENTRADA	0.18	KW
ROTACIÓN DE ENTRADA	1400	RPM
PAM DE ENTRADA	63B5	
PAR DE SALIDA	43.46	N.m
PAR NOMINAL	67.61	N.m
POTENCIA NOMINAL	0.28	KW
FACTOR DE SERVICIO	1.56	
EFICIENCIA DINÁMICA	0.59	




Cantidad de Aceite (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
0.15	0.15	0.15	0.15	0.15	0.15


Cargas Radiales y Axiales




n_2 [min-1]	FA [N]	FR [N]
200	240	1200
100	300	1500
50	380	1900
15	560	2800




Square flange FA




Square flange FB




Feet



Reaction arm



Single Shaft



b1	c1	d1	e1	m1	n1	t2	o1
8	50	25	53.5	92	153	28	M10

1400 rpm	N2	Relação	P1	FS	P1n	M2	Rend.	Fr max	Veio		Flanges de entrada				
	rpm	i	kW		kW	Nm	%	N	Entrada	Saída	63	71	80		
UMSG50	187	7,5	1,1	1,5	1,6	71	0,88	1805	19	25		B14/B5	B14/B5		
	140	10	1,1	1,1	1,2	70	0,86	1987				B14/B5	B14/B5		
	93	15	0,75	1,2	0,88	73	0,82	2274				B14/B5	B14/B5		
	70	20	0,75	0,9	0,68	72	0,79	2503				B14/B5	B14/B5		
	56	25	0,55	1,0	0,54	69	0,76	2696				B14/B5	B14/B5		
	47	30	0,55	1,0	0,57	83	0,72	2865				B14/B5	B14/B5		
	35	40	0,37	1,1	0,42	77	0,67	3153	14			B14/B5			
	28	50	0,37	0,9	0,34	73	0,63	3397				B14/B5	B14/B5		
	23	60	0,25	1,1	0,28	68	0,59	3610				B14/B5	B14/B5		
	18	80	0,25	0,9	0,22	64	0,53	3973				B14/B5	B14/B5		
	14	100	0,18	1,0	0,18	52	0,49	4280			11		B14/B5		