

MODELO	512A
Ø VEIO SAÍDA	30 mm
RÁCIO APROXIMADO	14
RÁCIO EXATO	14.21
VELOCIDADE SAÍDA	104 RPM
VELOCIDADE SAÍDA EXATA	103 RPM
POTÊNCIA ENTRADA	3.00 KW
ROTAÇÃO ENTRADA	1400 RPM
PAM ENTRADA	100B5
TORQUE SAÍDA	279.15 N.m
TORQUE NOMINAL	250.00 N.m
POTÊNCIA NOMINAL	2.7 KW
FATOR SERVIÇO	0.90
EFICIÊNCIA DINÂMICA	0.96

QUANTIDADE DE ÓLEO (L)

B3/H1	B6/H4	B7/H3	B8/H2	V5/H5	V6/H6
0.7	0.8	1.15	1.2	1.15	1.25

CARGAS RADIAIS E AXIAIS




n_2 [min-1]	F_A [N]	F_R [N]
300	460	2300
200	520	2600
120	620	3100
15	1000	5000

Universal Motors S.A.
Rua Comendador Brandão, 484
4495-375 Póvoa de Varzim
geral@universalmotors.pt
TEL.: 252 299 080

Universal Motors UK, Ltd
Unit E2, Meltham Mills Road
West Yorkshire HD9 4AR
enquiries@universalmotors-group.co.uk
TEL.: +44(0) 1484660222

Universal Motors SL
C/La Habana n.6 nave 4 PI Camporoso
28806 Alcala de Henares
info@universalmotors-group.es
TEL.: 918 864 213

Gearbox weight peso riduttore	With flange	11.7 kg
	With feet	11.9 Kg



Feet Code	Market reference	G	H	R	L	S	H1	O	øI	S2 only with motor flange	B5 max. Flange	kit code
B3	312/3	18	110	160	130	190	211	20	11	10 100/112B5 35 132B5	-	KC50.9.024
B4	30/35	20	130	180	149.5	216	231	18	14	15 132B5	-	KC60.9.024
S4	47-57	30	115	135	165	170	216	25	14	5 100/112B5 30 132B5	-	KC50.9.022
H3	023-233	30	130	135	135	185	231	25	14	15 132B5	-	KC50.9.025
M2	52/3	30	110	135-150	100	190	211	18	11	10 100/112B5 35 132B5	-	KC50.9.023

 Most popular types
Tipi più diffusi

The technical drawing illustrates the output shaft assembly with three main views:

- Front View (Left):** Shows a circular shaft end with a central hole. Dimensions include p_1 (hole diameter) and x (reference axis).
- Side View (Middle):** A cross-sectional view of the shaft assembly. Key dimensions shown are:
 - $8.5 \text{ with KC50.9.011}$: Total width of the assembly.
 - 2.5 : Width of the internal component.
 - h_1 : Height from the base to the top of the internal component.
 - d_1 : Diameter of the internal component's bore.
 - Detail Y**: Callout pointing to the interface between the internal component and the housing.
- End View (Right):** A perspective view of the shaft assembly. Key dimensions shown are:
 - a_1 : Overall length of the shaft.
 - b_1 , f_7 : Segment lengths along the shaft.
 - f_1 : Distance from the end face to the start of the threaded section.
 - c_1 : Threaded section length.
 - 57.5 : Distance from the end face to the center of the internal component.
 - k_1 : Total length of the housing.
 - 5.3 : Internal thread specification.
 - g_6 : Flange thickness.
 - $51.5 \text{ with KC50.9.011}$: Dimension for the internal component's position relative to the flange.

	Shaft - d1	p1	h1	x
Standard	ø 30x60	8	33	M10x22
On request A richiesta	ø 24x50	8	27	M8x19
	ø 25x50	8	28	M8x19
	ø 28x60	8	31	M8x19
	ø 35x60	10	38	M10x22

a1 ø	b1	c1	e1	f1	s1	kit code
160	110	14	130	3.5	11	KC50.9.011
200	130	13	165	3.5	11	KC50.9.012
250	180	15.5	215	4	14	KC50.9.013

With flange and feet only on request.
Ask for compatibility

[illegible][illegible]

5-16