

|                        |            |
|------------------------|------------|
| MODELO                 | 612A       |
| Ø VEIO SAÍDA           | 35 mm      |
| RÁCIO APROXIMADO       | 40         |
| RÁCIO EXATO            | 40.50      |
| VELOCIDADE SAÍDA       | 37 RPM     |
| VELOCIDADE SAÍDA EXATA | 36 RPM     |
| POTÊNCIA ENTRADA       | 1.50 KW    |
| ROTAÇÃO ENTRADA        | 1400 RPM   |
| PAM ENTRADA            | 90B14      |
| TORQUE SAÍDA           | 397.80 N.m |
| TORQUE NOMINAL         | 320.00 N.m |
| POTÊNCIA NOMINAL       | 1.2 KW     |
| FATOR SERVIÇO          | 0.80       |
| EFICIÊNCIA DINÂMICA    | 0.96       |

QUANTIDADE DE ÓLEO (L)

| B3/H1 | B6/H4 | B7/H3 | B8/H2 | V5/H5 | V6/H6 |
|-------|-------|-------|-------|-------|-------|
| 0.8   | 1     | 1.2   | 1.2   | 1.3   | 1.35  |

CARGAS RADIAIS E AXIAIS




| $n_2$ [min-1] | $F_A$ [N] | $F_R$ [N] |
|---------------|-----------|-----------|
| 300           | 560       | 2800      |
| 200           | 640       | 3200      |
| 120           | 760       | 3800      |
| 15            | 1300      | 6500      |

Universal Motors S.A.  
Rua Comendador Brandão, 484  
4495-375 Póvoa de Varzim  
[geral@universalmotors.pt](mailto:geral@universalmotors.pt)  
TEL.: 252 299 080

Universal Motors UK, Ltd  
Unit E2, Meltham Mills Road  
West Yorkshire HD9 4AR  
[enquiries@universalmotors-group.co.uk](mailto:enquiries@universalmotors-group.co.uk)  
TEL.: +44(0) 1484660222

Universal Motors SL  
C/La Habana n.6 nave 4 PI Camporoso  
28806 Alcala de Henares  
[info@universalmotors-group.es](mailto:info@universalmotors-group.es)  
TEL.: 918 864 213

|                                         |             |                |
|-----------------------------------------|-------------|----------------|
| <b>Gearbox weight</b><br>peso riduttore | With flange | <b>14.1 kg</b> |
|                                         | With feet   | <b>14.5 kg</b> |



| Feet Code | Market reference | G  | H   | R       | L     | S   | H1  | O  | Øl | S2 only with motor flange | B5 max. Flange | kit code     |
|-----------|------------------|----|-----|---------|-------|-----|-----|----|----|---------------------------|----------------|--------------|
| B4        | 412/3            | 20 | 130 | 180     | 149.5 | 216 | 242 | 18 | 14 | -                         | -              | KC60.9.024   |
| S4        | 47-57            | 30 | 115 | 135     | 165   | 170 | 227 | 25 | 14 | 13 132B5                  | -              | KC50.9.022   |
| M3        | 62/3             | 35 | 120 | 170+185 | 110   | 230 | 232 | 20 | 14 | 8 132B5                   | -              | KC60.9.023   |
| S7        | 77               | 35 | 140 | 170     | 205   | 204 | 252 | 8  | 14 | -                         | -              | KC60.9.029LM |
| H4        | 024-243          | 35 | 155 | 170     | 150   | 225 | 267 | 30 | 14 | -                         | -              | KC60.9.025   |

 Most popular types  
Tipi più diffusi

Technical drawing of the KC50.9.011 motor showing front, side, and detail views with dimensions.

**Front View (Left):** Shows the motor's base with dimensions  $p1$  (width) and  $x$  (center-to-center distance).

**Side View (Middle):** Shows the motor's profile with dimensions  $h1$  (total height),  $d1$  (base diameter), and a mounting flange with a thickness of 2.5. A callout indicates a total width of 8.5 with KC50.9.011.

**Detail Y (Right):** A detailed view of the mounting flange with dimensions  $a1$  (total height),  $b1$  (flange height),  $f7$  (flange thickness),  $f1$  (flange width),  $c1$  (flange offset), and a total width of 61.5 with KC50.9.011. The flange has a diameter of 16.3 and a total height of 96.

**\*Available output shaft / Albero di uscita**

**\*Available output shaft** / Albero di uscita

|                           | Shaft - d1 | p1 | h1 | x      |
|---------------------------|------------|----|----|--------|
| Standard                  | ø 35x70    | 10 | 38 | M10x22 |
| On request<br>A richiesta | ø 28x60    | 8  | 31 | M8x20  |
|                           | ø 30x60    | 8  | 33 | M10x22 |
|                           | ø 38x70    | 10 | 41 | M10x25 |
|                           | ø 40x80    | 12 | 43 | M12x28 |

### Available output flanges / flange di uscita

| a1 Ø | b1  | c1   | e1  | f1  | s1 | kit code   |
|------|-----|------|-----|-----|----|------------|
| 160  | 110 | 14   | 130 | 3.5 | 11 | KC50.9.011 |
| 200  | 130 | 13   | 164 | 3.5 | 11 | KC50.9.012 |
| 250  | 180 | 15.5 | 215 | 4   | 14 | KC50.9.013 |

With flange and feet only on request. Ask for compatibility

With flange and feet  
only on request.  
Ask for compatibility

Technical drawing of the B14 motor flange assembly, showing side and top views with dimensions.

**Side View Dimensions:**

- Total width: 219
- Height: 96
- Central shaft diameter:  $\varnothing 35$  h6
- Shaft length: 10
- Flange height: 15.5
- Flange width: 60
- Base diameter: 70
- Base height: 12.5
- Mounting hole diameter: 5
- Mounting hole pitch: 60

**Top View Dimensions:**

- Flange side length: 181.5
- Central circular opening diameter:  $\varnothing 123$
- Mounting hole diameter: N.5 M10x17
- Mounting hole pitch: 65
- Angle between mounting holes: 50°

**Labels:**

- Riduttore base
- Suggested B14 motor flanges
- M10x22

[illegible]

| <b>B5 Motor Flanges</b> | <b>A</b> | <b>C<sub>max</sub></b> | <b>g6</b> | <b>k1</b> | <b>kit code</b> | <b>k1 with KC50.9.011</b> | <b>B14 Motor Flanges</b> | <b>A</b> | <b>C<sub>max</sub></b> | <b>g6</b> | <b>k1</b> | <b>kit code</b> | <b>k1 with KC50.9.011</b> |
|-------------------------|----------|------------------------|-----------|-----------|-----------------|---------------------------|--------------------------|----------|------------------------|-----------|-----------|-----------------|---------------------------|
| 71 B5                   | 237.5    | 251.3                  | 160       | 240       | K023.4.041      | 246                       | 80 B14                   | 239.5    | 231.3                  | 120       | 242       | K085.4.046      | 248                       |
| 80/90 B5                | 239.5    | 271.3                  | 200       | 242       | K023.4.042      | 248                       | 90 B14                   | 239.5    | 241.3                  | 140       | 242       | K085.4.045      | 248                       |
| 100/112 B5              | 248.5    | 296.3                  | 250       | 251       | K023.4.043      | 257                       | 100/112 B14              | 248.5    | 251.3                  | 160       | 251       | K085.4.047      | 257                       |
| 132 B5                  | 269.5    | 321.3                  | 300       | 269       | KC51.4.043      | 275                       | 132 B14                  | 269.5    | 271.3                  | 200       | 269       | KC51.4.041      | 275                       |